


# SEE THE WHOLE LINK




Debug and validate active link behavior across electrical and protocol layers.

**CrossSync™ PHY**  
Cross-layer Analysis for PCI Express®

# THE CrossSync™ PHY CONCEPT

Interoperability issues can lead to finger-pointing exercises that cost money and time-to-market. Teledyne LeCroy CrossSync PHY software and interposers merge the functions of your Teledyne LeCroy protocol analyzer and oscilloscope - giving insight into link behavior that no other instrument can provide.



## Validate and debug active link operation

- CrossSync PHY capable interposers enable observation of both electrical and protocol behavior without disturbing the link
- Sideband signals, reference clock, and power rails are all easily accessible to oscilloscope probes
- Optional high-bandwidth oscilloscope probing points for PCI Express data lanes

## Quickly resolve interoperability issues by capturing the entire protocol stack

- Trigger protocol analyzer and oscilloscope captures on the same high-level event
- Easily measure timing relationships between protocol and electrical domains
- Faster root-cause analysis means fewer costly finger-pointing exercises

## Analyze link training with integrated physical and protocol views

- Observe electrical-level results of protocol-level commands
- Combined navigation means always knowing which protocol and electrical behaviors happen at the same time
- No single instrument can deliver this level of cross-layer insight into link training behavior

# MORE VISIBILITY INTO...



Correlated electrical and protocol views of a link speed change from 8 to 16 GT/s.

## Dynamic Link Behavior

- Characterize entire boot sequence with visibility into sideband signals, reference clock, data lanes, and power rails.
- Observe speed changes in both electrical and protocol domains.
- Trigger on problematic link training behaviors and analyze their consequences through the entire protocol stack.
- Save, recall, and re-analyze linked oscilloscope and protocol analyzer traces.



Analyzing exit from L1.2 including reference clock and CLKREQ# behavior.

## Power Management Transitions

- Quick and easy triggering and capture of both protocol and electrical behavior as a device enters or exits low-power states.
- Precise timing measurements between protocol commands and electrical behaviors of reference clock and high-speed data lines.
- Dynamic power analysis through Power Management transitions including L1 substates.




Dynamic rail voltage, current and power measurements as lane changes speed to 16 GT/s.

## Dynamic Power Characterization

- CrossSync PHY interposers have built-in rail voltage and current measurement points.
- Voltage and current waveforms are synchronized and time-correlated to protocol analyzer trace.
- Oscilloscope tools enable measurement of dynamic power consumption and power integrity metrics.
- Compatible with RP4030 Active Voltage Rail probe for low-noise measurement of voltage rails with high bandwidth and low loading.

# CrossSync™ PHY INTEGRATED ANALYSIS SOFTWARE


The CrossSync PHY software option for your Teledyne LeCroy oscilloscope enables precise, intuitive navigation between time-correlated protocol analyzer and oscilloscope traces.



1. CrossSync PHY navigation bar makes clear the timing relationship between linked protocol analyzer and oscilloscope captures
2. One or many oscilloscope acquisition segments are represented in the navigation bar
3. Protocol analyzer trace represented in the navigation bar
4. Common trigger point ensures precise timing alignment between protocol trace, oscilloscope acquisitions, and navigation bar view
5. Oscilloscope timebase and protocol analyzer acquisition window remain synchronized while navigating through the combined acquisition, for total confidence in timing behavior
6. Selecting a packet on the protocol trace enables zoom traces on the oscilloscope to the same time window, enabling sub-packet-level measurement precision

# CrossSync™ PHY CAPABLE PCI EXPRESS INTERPOSERS

CrossSync PHY capability enhances Teledyne LeCroy's industry-leading set of protocol analysis interposers by adding high-fidelity oscilloscope probing points with simple and convenient signal access.



1. Transparent signal path between host and endpoint, with convenient connections to both protocol analyzer and oscilloscope
2. Simple, low-loading direct connection to high-speed lanes for Teledyne LeCroy DH series oscilloscope probes up to 30 GHz bandwidth – no soldering required
3. Easy access to all sideband signals
4. High-bandwidth voltage and current connections for monitoring dynamic power rail behavior
5. High-fidelity buffered reference clock connection for observing clock behavior during power-up and low-power states

PE617UIA-X PCIe 6.0 CEM interposer shown with PE6817ACA-X high-speed probing upgrade

## CrossSync PHY interposers for popular PCI Express form factors

See Ordering Information on page 8 for full configuration

### CEM form factor



PE6817ACA-X PCIe 6.0 CEM x16 interposer

### M.2 form factor



PE222UIA PCIe 5.0 M.2 M-Key Interposer

### EDSFF form factor



PE243UIA-X G5x4 EDSFF E1.S Interposer  
PE241UIA-X G5x8 EDSFF E1.L Interposer  
PE240UIA-X G5x16 EDSFF E3.x Interposer

### U.2/U.3 form factor



PE221UIA-X PCI Express 5.0 U.2/U.3 12 inch Interposer

# COMPATIBLE PROTOCOL ANALYZERS



## Summit M616

- Protocol Analyzer and Exerciser for PCI Express 6.0, NVMe, and CXL (Compute Express Link)
- Supports up to x16 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, 16 GT/s, 32 GT/s and 64 GT/s
- Trace buffer up to 64 GB



## Summit T516

- Protocol Analyzer for PCI Express 5.0, NVMe, and CXL (Compute Express Link)
- Supports up to x16 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, 16 GT/s and 32 GT/s
- Trace buffer up to 256 GB



## Summit M5x

- Protocol Analyzer for PCI Express 5.0, NVMe, and CXL (Compute Express Link)
- Supports up to x8 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, and 16 GT/s
- Trace buffer up to 128 GB



## Summit T54

- Protocol Analyzer for PCI Express 5.0, NVMe, and CXL (Compute Express Link)
- Supports x1, x2 and x4 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, 16 GT/s and 32 GT/s
- Trace buffer up to 64 GB
- Can be cascaded to support x8 Link Widths with up to 128 GB of trace buffer



## Summit T416

- Protocol Analyzer for PCI Express 4.0 and NVMe
- Supports up to x8 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, and 16 GT/s
- Trace buffer up to 128 GB



## Summit T48

- Protocol Analyzer for PCI Express 4.0 and NVMe
- Supports up to x8 Links at data rates of 2.5 GT/s, 5 GT/s, 8 GT/s, and 16 GT/s
- Trace buffer up to 64 GB

# COMPATIBLE OSCILLOSCOPE PRODUCTS



## WaveMaster 8000HD

- Up to 65 GHz real time bandwidth with 12-bit resolution
- Supports PCI Express measurements to PCIe 7.0 and beyond
- Class-leading PC system, so less time spent waiting for measurements to complete




## DH Series High-bandwidth Differential Probes

- Connect directly to CrossSync PHY interposers with no soldering required
- Up to 30 GHz bandwidth, low noise, low loading
- Other tips available: solder-in (standard and high-sensitivity), high-temperature solder-in, handheld browser, QuickLink adapter



## RP4030 Active Voltage Rail Probe

- Connects directly to CrossSync PHY interposers with no soldering required
- 4 GHz bandwidth with  $\pm 30V$  Offset Capability
- Low attenuation for very low noise
- 50 k $\Omega$  DC Input Impedance for low loading



## QualiPHY PCIe Test Automation Software

- Automates WaveMaster 8000HD oscilloscopes to perform PCI Express compliance and characterization testing
- Compatible with Anritsu MP1900A Signal Quality Analyzer for complete receiver test calibration and execution
- Available for PCI Express 3.0, 4.0, 5.0, and 6.0



## PCI Express Decode

- Decode PCI Express signals up to data link layer directly in the oscilloscope user interface
- Intuitive, Color-Coded Overlays
- Interactive Table Summarizes Results

# ORDERING INFORMATION

## Product Description

## Product Code

### Oscilloscope Software Options (enables CrossSync PHY functionality on installed CrossSync software)

PCIe CrossSync PHY protocol analyzer synchronization for WaveMaster/SDA 8000HD

WM8KHD-CROSSSYNC-PHY-PCIE

### CrossSync PHY capable PCI Express Interposers

#### PCI Express 6.0 - CEM form factor

PCIe 6.0 CEM x16 interposer (Includes sideband, power rail and REFCLK probing points, no high-speed probing points)	PE6117UIA-X
Upgrade PE6117UIA-X to add probing points on all 32 high-speed lanes	PE6817ACA-X
Probe tip to connect DH series oscilloscope probe to PE6817ACA-X	DH-CSPHY-PCIE6

#### PCI Express 5.0 - CEM form factor

PCIe 5.0 CEM x16 interposer (Includes sideband, power rail and REFCLK probing points, no high-speed probing points)	PE230UIA-X
Upgrade PE230UIA-X to add probing points on all 32 high-speed lanes	PE120ACA-X
Probe tip to connect DH series oscilloscope probe to PE120ACA-X	DH-CSPHY-PCIE5-CEMx16

#### PCI Express 5.0 - EDSFF form factor

PCIe 5.0 x4 EDSFF E1.S Interposer	PE243UIA-X
PCIe 5.0 x8 EDSFF E1.L Interposer	PE241UIA-X
PCIe 5.0 x16 EDSFF E3.x Interposer (Includes sideband, power rail and REFCLK probing points, no high-speed probing points)	PE240UIA-X
Upgrade PE243UIA-X, PE241UIA-X, or PE240UIA-X to add probing points on all 32 high-speed lanes	PE135ACA-X
Probe tip to connect DH series oscilloscope probe to PE135ACA-X	DH-CSPHY-PCIE5-EDSFF

#### PCI Express 5.0 - U.2/U.3 form factor

PCIe 5.0 U.2/U.3 12 inch Interposer (Includes sideband, power rail and REFCLK probing points, no high-speed probing points)	PE221UIA-X
Upgrade PE221UIA-X to add probing points on all 32 high-speed lanes	PE130ACA-X
Probe tip to connect DH series oscilloscope probe to PE130ACA-X	DH-CSPHY-PCIE5-U2U3

#### PCI Express 5.0 - M.2 form factor

PCIe 5.0 M.2 M-Key Interposer - CrossSync PHY capable (Incl. sideband, power rail and REFCLK probing points, no high-speed probing points)	PE222UIA-X
PCIe 5.0 M.2 M-Key Interposer with oscilloscope probe Lane 0	PE222UIA-1PHY
PCIe 5.0 M.2 M-Key Interposer with oscilloscope probe Lane 0, 1	PE222UIA-2PHY
PCIe 5.0 M.2 M-Key Interposer with oscilloscope probe Lane 0, 1, 2, 3	PE222UIA-4PHY

#### PCI Express 4.0 - M.2 form factor

PCIe 4.0 M.2 M-Key Interposer - CrossSync PHY capable (Incl. sideband, power rail and REFCLK probing points, no high-speed probing points)	PE210UIA-X
PCIe 4.0 M.2 M-Key Interposer with oscilloscope probe Lane 0	PE210UIA-1PHY
PCIe 4.0 M.2 M-Key Interposer with oscilloscope probe Lane 0, 1	PE210UIA-2PHY
PCIe 4.0 M.2 M-Key Interposer with oscilloscope probe Lane 0, 1, 2, 3	PE210UIA-4PHY

### Compatible Protocol Analyzers

Protocol Analyzer for PCIe 6.0, NVMe, and CXL up to x16 link	Summit M616
Protocol Analyzer for PCIe 5.0, NVMe, and CXL up to x16 links	Summit T516
Protocol Analyzer for PCIe 5.0, NVMe, and CXL up to x8 links	Summit M5x
Protocol Analyzer for PCIe 5.0, NVMe, and CXL up to x4 links	Summit T54
Protocol Analyzer for PCIe 4.0 and NVMe up to x16 links	Summit T416
Protocol Analyzer for PCIe 4.0 and NVMe up to x8 links	Summit T48

Probes and cables not included - consult your Teledyne LeCroy sales representative for protocol analyzer configuration details.

### Recommended Oscilloscopes

CrossSync PHY is compatible with WaveMaster 8000HD series oscilloscopes.

#### PCI Express 6.0 - CrossSync PHY and Compliance Test capable

50 GHz (or higher), 320 GS/s, 400 Mpts/Ch WaveMaster 8000HD	WaveMaster 8500HD
---	-------------------

#### PCI Express 5.0 - CrossSync PHY and Compliance Test capable

50 GHz (or higher), 320 GS/s, 400 Mpts/Ch WaveMaster 8000HD	WaveMaster 8500HD
---	-------------------

#### PCI Express 4.0 - CrossSync PHY and Compliance Test capable

25 GHz (or higher), 160 GS/s, 200 Mpts/Ch WaveMaster 8000HD	WaveMaster 8250HD
---	-------------------

#### PCI Express 3.0 - CrossSync PHY and Compliance Test capable

13 GHz (or higher), 80 GS/s, 2000 Mpts/Ch WaveMaster 8000HD	WaveMaster 8130HD
---	-------------------

### Recommended Oscilloscope Probes

13 GHz differential probe with ProLink interface	DH13-PL
20 GHz differential probe with ProLink interface	DH20-PL
25 GHz differential probe with ProAxial interface	DH25-PX
30 GHz differential probe with 2.92 mm interface	DH30-2.92MM
30 GHz differential probe with ProAxial interface	DH30-PX
Power/Voltage Rail Probe. 4 GHz bandwidth, 1.2x attenuation, $\pm 30$ V offset, $\pm 800$ mV	RP4030

### Recommended Oscilloscope Software Options

QualiPHY PCIe 6.0 Tx/Rx/LEQ Compliance Software Option (incl QPHY-PCIE5-Tx-RX, QPHY-PCIE4-Tx-RX and QPHY-PCIE3-Tx-RX)	QPHY-PCIE6-TX-RX
QualiPHY PCIe 5.0 Tx/Rx/LEQ Compliance Software Option (incl QPHY-PCIE4-Tx-RX and QPHY-PCIE3-Tx-RX)	QPHY-PCIE5-TX-RX
QualiPHY PCIe 4.0 Tx/Rx/LEQ Compliance Software Option (incl QPHY-PCIE3-Tx-RX)	QPHY-PCIE4-TX-RX
QualiPHY PCIe 3.0 Tx/Rx/LEQ Compliance Software Option	QPHY-PCIE3-TX-RX

### Customer Service

Teledyne LeCroy oscilloscopes and probes are designed, built, and tested to ensure high reliability. In the unlikely event you experience difficulties, our digital oscilloscopes are fully warranted for three years and our probes are warranted for one year.

This warranty includes: • No charge for return shipping • Long-term 7-year support • Upgrade to latest software at no charge



1-800-5-LeCroy  
teledyneleeroy.com

Local sales offices are located throughout the world.  
Visit our website to find the most convenient location.