


MEMS 192X192 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Network Grade



DiCon's **Optical Switching System (OSS)** is an all-optical non-blocking cross-connect switch. This rack-mount device is designed with DiCon's proprietary 3D MEMS mirror technology and delivers industry-leading optical performance. The unit works without any position sensor or feedback loop, and the optical signals can pass through the equipment without any observable dithering artifacts. The **OSS** can switch repeatedly with great accuracy and maintain long-term connectivity with superior stability even when there is no optical signal in the fiber.

The chassis is compact, taking minimal rack space. It is also lightweight and can be picked up easily for installation. The **OSS** comes with multiple control interfaces so authorized administrators can automate network management and set user permissions in a Software Defined Network (SDN). This product can be ordered in standard simplex or duplex configurations, and customized port arrangements are available upon request. Optical power monitors and attenuators can be added to each path as options.

Key Features

- Market Leading Performance with Recognized Reliability
- Low Loss with High Stability & No Dithering Artifacts
- Compact, Lightweight, Easy to Transport
- Switches Fast & Consumes Low Power
- Operates Bi-Directionally & Works with Dark Fibers
- Supports Software Defined Networks

Applications

- Optical Network Management
- Quantum Communications
- Data Center Interconnect
- AI (Artificial Intelligence) Networks
- LLM (Large Language Models) Machine Training
- Cyber Security & Monitoring
- Network Test Automation

ORDERING INFORMATION

OSS - N - - **9** - **C** - - -

Grade	N	Network
Configuration	S192x192	Simplex 192x192
	SMxN	Simplex (M, N≤192)
	D192	Duplex 192 Ports
	DM	Duplex (M≤192)
Function	S	Matrix Switch Only
	MS	With Input Power Monitor
	SN	With Output Power Monitor
	MSN	With Both Power Monitors
Fiber Type	9	9/125 μm SMF
	<i>*Other fiber options available upon request</i>	
Optimized Wavelength Range	C	1530-1625 nm
Chassis Height	3U	3U
	4U	4U
	6U	6U
	<i>*Contact Sales for assistance</i>	
Power	A1	AC 90-264V Single
	D1	DC -48V Single
	A2	AC 90-264V Redundant
	D2	DC -48V Redundant
Connector Type	LC	LC/UPC
	LC/APC	LC/APC
	RLC	LC/UPC on Removable Panel
	RLC/APC	LC/APC on Removable Panel
	HLC	High Density LC UPC
	HLC/APC	High Density LC APC
	M8	MTP/MPO-8 APC
	M12	MTP/MPO-12 APC
	<i>*Other connector types available upon request</i>	
Connector Location	F	Front
	R	Rear

MEMS 192X192 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Network Grade

OPTICAL SPECIFICATIONS

Wavelength Range	1260 to 1675 nm
Insertion Loss ¹	< 1.2 dB
Insertion Loss (with 1 OPM)	< 1.6 dB
Insertion Loss (with 2 OPM)	< 2.0 dB
Loss Repeatability ²	+/- 0.03 dB
Connection Stability ³	+/- 0.03 dB
PDL, C+L Band (1530-1625 nm)	< 0.1 dB
PDL, C+L Band with OPM	< 0.3 dB
WDL, C+L Band (1530-1625 nm)	< 0.3 dB
Crosstalk	< -60 dB
Data Latency	< 15 ns
Back Reflection	< -50 dB
Switching Time, All Channels	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Input Power Range	Dark to +27 dBm
OPM Dynamic Range	-50 to +22 dBm
OPM Accuracy	+/-0.2 dB @ > -30dBm +/-0.5 dB @ > -50dBm

1. Measured at optimized λ (e.g. 1550 nm), 25°C, excluding connectors (Each pair of connectors will add extra 0.2 dB loss.)

2. Over 100 cycles

3. 1 Hz sampling rate for 15 min

ELECTRICAL SPECIFICATIONS

Power Consumption	< 55W Steady State < 65W at Startup
Power Supply Options	Redundant Power Supply, 90-264 VAC or -48 VDC
Network Interface Card	RJ45 Dual Redundant Gigabit Ethernet
SDN & Automation Interfaces	REST API, NETCONF, SNMPv3, TL1, Web GUI, RS232

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

MECHANICAL SPECIFICATIONS

19" Chassis Depth	559 mm (22")
19" Chassis Height	3U (with HD LC)