


MEMS 600X600 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Network Grade



DiCon’s **Optical Switching System (OSS)** is an all-optical non-blocking cross-connect switch. This rack-mount device is designed with DiCon’s proprietary 3D MEMS mirror technology and delivers industry-leading optical performance. The unit works without any position sensor or feedback loop, and the optical signals can pass through the equipment without any observable dithering artifacts. The **OSS** can switch repeatedly with great accuracy and maintain long-term connectivity with superior stability even when there is no optical signal in the fiber.

The chassis is compact, taking minimal rack space. It is also lightweight and can be picked up easily for installation. The **OSS** comes with multiple control interfaces so authorized administrators can automate network management and set user permissions in a Software Defined Network (SDN). This product can be ordered in standard simplex or duplex configurations, and customized port arrangements are available upon request. Optical power monitors and attenuators can be added to each path as options.

Key Features

- Market Leading Performance with Recognized Reliability
- Low Loss with High Stability & No Dithering Artifacts
- Easy to Transport
- Switches Fast & Consumes Low Power
- Operates Bi-Directionally & Works with Dark Fibers
- Supports Software Defined Networks

Applications

- Optical Network Management
- Quantum Communications
- Data Center Interconnect
- AI (Artificial Intelligence) Networks
- LLM (Large Language Models) Machine Training
- Cyber Security & Monitoring
- Network Test Automation

ORDERING INFORMATION

OSS - N - 9 - 9 - 9 - 9 - 9 - 9

Grade		
N	Network	
Configuration		
S600x600	Simplex 600x600	
SMxN	Simplex (M, N≤600)	
D600	Duplex 600 Ports	
D#	Duplex (#≤600)	
Function		
Simplex	S	Matrix Switch Only
	SA	VOA Only
	MS	M Side Power Monitor
	MSA	M Side Power Monitor & VOA
	SN	N Side Power Monitor
Duplex	SAN	N Side Power Monitor & VOA
	MSN	Both Sides Power Monitor
	MSAN	Both Sides Power Monitor & VOA
	D	Matrix Switch Only
	DA	VOA Only
	DP	Power Monitor (B Ports / Outputs)
	DAP	Power Monitor & VOA (B Ports / Outputs)
	Fiber Type	
	9	9/125 μm SMF
	*Other fiber options available upon request	
Test Wavelength		
O	1310 nm	
C	1550 nm	
L	1590 nm	
*Use "/" to add multiple wavelengths. E.g., O/C or O/C/L		
Chassis Type		
5U	5U	
6U	6U	
8U	8U	
*Please consult DiCon **See "Mechanical Specifications"		
Power		
A1	AC 100-240V Single	
D1	DC -48V Single	
A2	AC 100-240V Redundant	
D2	DC -48V Redundant	
Connector Type		
LC	LC/UPC	
LC/APC	LC/APC	
RLC	LC/UPC on Removable Panel	
RLC/APC	LC/APC on Removable Panel	
HLC	High Density LC/UPC	
HLC/APC	High Density LC/APC	
M8F	MTP/MPO-8 Female APC	
M8M	MTP/MPO-8 Male APC	
M12F	MTP/MPO-12 Female APC	
M12M	MTP/MPO-12 Male APC	
M24F	MTP/MPO-24 Female APC	
M24M	MTP/MPO-24 Male APC	
*Other connector types are available upon request		
Connector Location		
F	Front	
R	Rear	

MEMS 600X600 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Network Grade

OPTICAL SPECIFICATIONS¹

Operating Wavelength	1260 to 1680 nm
Insertion Loss ²	< 2.1 dB
Insertion Loss (with 1 OPM) ²	< 2.4 dB
Insertion Loss (with 2 OPM) ²	< 2.7 dB
Loss Repeatability ³	+/- 0.03 dB
Connection Stability ^{4,5}	+/- 0.03 dB
PDL ⁵	< 0.1 dB
PDL with OPM ⁵	< 0.3 dB
WDL ^{5,6}	< 0.3 dB
Crosstalk ⁵	< -60 dB
Data Latency ⁵	< 15 ns
Back Reflection	< -50 dB
Optical Transition Time ^{5,7}	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Input Power Range	Dark to +27 dBm
OPM Dynamic Range	-50 to +22 dBm
OPM Relative Accuracy	+/-0.2 dB @ > -30dBm +/-0.5 dB @ > -50dBm

1. Measured separately for each Test Wavelength
2. Measured with 3-jumper method or equivalent. See TIA/EIA 526-7.
3. Over 100 cycles
4. 1 Hz sampling rate for 15 min
5. Met by design, not measured
6. Test Wavelength +/-20nm
7. Optical transition time for all ports switching concurrently, not including command processing overhead

ELECTRICAL SPECIFICATIONS

Power Consumption*	< 100W Steady State < 110W at Startup
Power Supply Options	Redundant Power Supply, 100-240 VAC or -48 VDC
Network Interface Card	RJ45 Dual Redundant Gigabit Ethernet
SDN & Automation Interfaces	REST API, NETCONF, SNMPv3, TL1, Web GUI, RS232

*Power is measured with 2 OPM

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

MECHANICAL SPECIFICATIONS

Chassis Width	483 mm (19")
Chassis Depth*	435 mm (17") 559 mm (22") 762 mm (30") 889 mm (35") 1016 mm (40")
Chassis Height	5U (with MTP/MPO-8)

*Please consult DiCon

