



## FEATURES

- Stabilized Visible Laser
- Battery Operated - 9 Volt
- 1mW Laser Diode @ 650nm
- Continuous Wave or Pulsed Wave
- Ruggedized Rubber Holster
- Singlemode or Multimode Use

## CONNECTOR STYLES

- 2.5mm Universal Adapter - (Singlemode & Multimode)(SC, FC, ST)
- LC - (Singlemode & Multimode)
- FC/APC - Singlemode
- SC/APC - Singlemode
- MT-RJ - Singlemode & Multimode

## SPECIFICATIONS

<b>Outpower</b>	1mW min	<b>Pulse Rate</b>	1Hz
<b>Wavelength</b>	650nm Typ	<b>Operating Temperature</b>	-10° to + 50° Celsius
<b>Battery</b>	9 Volt Alkaline	<b>Weight</b>	7.5 oz
<b>Battery Life (typical)</b>	30hrs continuous 40hrs modulated	<b>Size</b>	6.25"L x 3.25"W x 1.25"D
<b>Range</b>	5km - Multimode 7km - Singlemode	<b>Emission Indicator</b>	Power indicator in sync when laser in use

## ORDERING INFORMATION

<b>OF-1000-UF</b>	Visual Fault Locator with 2.5mm Universal Adapter (MM & SM)
<b>OF-1000U-LC</b>	Visual Fault Locator with LC Adapter (MM & SM)
<b>OF-1000U-FCA</b>	Visual Fault Locator with FC/APC Adapter (SM)
<b>OF-1000U-SCA</b>	Visual Fault Locator with SC/APC Adapter (SM)
<b>OF-1000U-MTRJ</b>	Visual Fault Locator with MT-RJ Adapter (MM & SM)