

O-Band Bismuth-doped Fiber Amplifier (Multi-Channel)

Key Features

- High output power
- Similar gain & noise figure as typical EDFA
- Lower power consumption compared to conventional Raman amplifier
- Distortion-free amplification



2U Rackmount Casing




Others

Description

Amonics' O-band Bismuth-doped fiber amplifier (BDF) uses bismuth-doped fiber as the gain medium. The multi-channel BDF features flattened gain across the operating wavelength range and very low noise figure. The silica-based Bismuth-doped fiber offers the similar fundamental advantages as erbium-doped fiber used for amplification in the C and L bands.

The turnkey microprocessor-controlled BDFs provide illustrative alarms and status indicators. An integrated RS232 computer interface enables easy control, diagnostic functions and data acquisition.

Application



- Datacom Network



ISO 9001 : 2015
Certificate No.: CC 5346

Our product is manufactured under a HKQAA ISO 9001 certified quality management system. The ISO 9001:2015 certification applies to the Hong Kong production site only.

O-Band Bismuth-doped Fiber Amplifier (Multi-Channel)

Specifications

Model	ABDFA-O-S-DWDM-19	ABDFA-O-L-DWDM-20
Operating Wavelength	1260 nm to 1340 nm	1280 nm to 1360 nm
Composite Input Power	-30 to 0 dBm	-30 to 0 dBm
Composite Output Power @ 0 dBm composite input power	Min. 19 dBm	Min. 20 dBm
Noise Figure @ 0 dBm composite input power	Typ. 6.5 dB, Max. 7.0 dB	Typ. 6.5 dB, Max. 7.0 dB
Gain Flatness	Max. ± 1.5 dB @ 1270 nm – 1330 nm	Max. ± 1.5 dB @ 1310 – 1350 nm
Input / Output Isolation	Min. 30 dB	Min. 30 dB
Control Mode	ACC	ACC

General Parameters

	Value
Operation Temperature	0 to +40 °C
Storage Temperature	-10 to +70 °C
Power Supply	90 – 240 VAC, 47 – 63 Hz
Rackmount Dimensions	2U Half Rack: 200(W) x 376(D) x 88(H) mm; 1U: 485(W) x 360(D) x 45(H) mm; 2U: 485(W) x 360(D) x 90(H) mm
Mechanical Safety Control	Key-lock switch, BNC interlock key
Optical Power Monitoring	Output power, Input power (optional)
Remote Control Port	DB-9 female (RS232), Control software included, RJ-45 (TCP/IP Ethernet) (optional)
Protection	Pump Power Protection
Optical Connector	FC/APC, FC/UPC, SC/APC, SC/UPC
Optical Fiber	SMF-28

Ordering Information

Product Code	ABDFA-O-S-DWDM-aa-b-cc ABDFA-O-L-DWDM-aa-b-cc	aa : Composite Output Power in dBm b : B for 2U Half Rack, R for 19" Rackmount cc : FA for FC/APC, FC for FC/UPC, SA for SC/APC, SC for SC/UPC
--------------	--	--

Amonics undertakes continuous and intensive product development to ensure its product performance at the highest technical standards. As a result, the specifications in this document are subject to change without notice.

Amonics Limited (Hong Kong)

14/F, Lee King Industrial Building, 12 Ng Fong Street,
San Po Kong, Kowloon, Hong Kong
Tel :+852 2428 9723 Fax :+852 2428 9704

Beijing Amonics Co. Ltd. (Beijing)

Room 902, Unit 1 Joy Mansion, NO.99 Chaoyang North Road, Beijing China 100123
Tel :+86 10 8478 3386 Fax :+86 10 8478 3396
Email: contact@amonics.com Website: www.amonics.com

