



MGL-FN-556/1~200mW

**LD PUMPED ALL-SOLID-STATE
YELLOW GREEN LASER
AT 556nm**

Yellow green laser at 556nm is made features of ultra compact, long lifetime, low cost and high stability, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	556 ± 1
Output power (mW)	>1, 5, 10, 20, ..., 200
Transverse mode	Near TEM ₀₀
Operating mode	CW
Power stability (rms, over 4 hours)	<3%, <5%, <10%
Warm-up time (minutes)	<10
M ² factor	<1.2
Beam divergence, full angle (mrad)	<1.5
Beam diameter at the aperture (mm)	~2.0
Beam height from base plate (mm)	27.4
Polarization ratio	>100:1 (0 or 90 degree)
Pointing stability after warm-up (mrad)	<0.05
Operating temperature(°C)	10~35
Power supply (90-264VAC or 5VDC)	PSU-H-LED PSU-H-FDA
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option
Expected lifetime (hours)	10000
Warranty	1 year



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MXL-FN-556	PSU-H-LED	PSU-H-FDA
197(L)×70(W)×50(H), 2.0 kg	268 (L) ×145 (W) ×106 (H) mm ³ , 2.6 kg	238 (L) ×146(W) ×102 (H) mm ³ , 2.3 kg