



MLL-FN-721 / 1~100mW



**LD PUMPED ALL-SOLID-STATE  
LOW NOISE RED LASER  
AT 721nm**

Low noise red laser at 721nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, and scientific research etc.



SPECIFICATIONS

Wavelength (nm)	721±1	
Operating mode	CW	
Output power (mW)	>1, 10, 20, ... ,50	>50, ... , 100
Power stability (rms, over 4 hours)	<3%, <5%	<3%, <5%, <10%
Transverse mode	TEM <sub>00</sub>	
M <sup>2</sup> factor	<1.2	
Noise of amplitude (rms, 20Hz~20MHz)	<1%	
Beam diameter at the aperture (1/e <sup>2</sup> , mm)	~2.0	
Beam divergence, full angle (mrad)	<1.5	
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)	
Warm-up time (minutes)	<10	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MLL-FN-721	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm<sup>3</sup>, 1.5 kg</p>	<p>275(L) ×145(W) ×104(H) mm<sup>3</sup>, 2.3 kg</p>