

Features:

- fiber-to-fiber optical gain of more than 25 dB
- output power of up to 13 dBm
- -3 dB optical gain bandwidth of up to 60 nm

Package: Butterfly (DBUT)

Additional & customized:

- PM fiber pigtails
- FC/APC terminated pigtails

Specifications
(nominal stabilization temperature +25 °C)

Parameter	Min.	Typ.	Max.
Forward current, mA	-	-	220
Forward voltage, V	-	-	2.5
Output optical power, dBm	-	-	13.0
Central wavelength λ_c , nm	-	870	-
-3 dB optical gain bandwidth, nm	-	58	-
Gain ripple, dB	-	< 0.1	-
Small signal gain, dB	-	-	25
Polarization dependent gain, dB	-	7.0	-





The following part numbers should be used when **ordering**:

SOA-352-870-(a)-(b),
 where:
 a – package type (DBUT),
 b – fiber type (SM or PM).

Example: SOA-352-870-DBUT-SM.

All specifications are subject to change without notice.

PERFORMANCE EXAMPLES



Continues on next page →

Performance examples (continued)

POWER BOOSTER PERFORMANCE EXAMPLES
 Output spectra at $P_{input}=2.0mW$, spectral $FWHM_{input}=0.03nm$

