


## PRODUCT DETAILS

Eoptolink's 100G CWDM4 2km QSFP28 Optical Transceiver



# EOLQ-161HG-02-1

Single-Mode, 100G QSFP28  
With LC interface



## Product Description

Eoptolink's EOLQ-161HG-02-1 QSFP28 transceiver module is designed for use in 100 Gigabit Ethernet links over 2km single mode fiber. The implementation of a 4 channels TOSA and ROSA to create a CWDM4 transceiver. The 100G CWDM4 QSFP28 is characterized by a 4x25Gbps (NRZ) electrical interface, a 4x25Gbps DFB-based CWDM transmitter and duplex LC connector. The electrical interface of the module is compliant with the CAUI-4 interface as defined by IEEE 802.3bm, and the form factor, optical/electrical connection and digital diagnostic interface compliant with CWDM4 MSA and QSFP28 MSA.

## Features

- Supports 103Gbps
- Single 3.3V Power Supply
- Power dissipation < 3.5W
- Up to 2km over SMF
- 4x25G electrical interface
- Duplex LC receptacles
- Commercial case temperature range of 0°C to 70°C
- 4x25Gbps DFB-based CWDM transmitter
- PIN and TIA array on the receiver side
- I2C interface with integrated Digital Diagnostic Monitoring
- Safety Certification: TUV/UL/FDA\*1
- RoHS Compliant

## Applications

- 100G CWDM4 applications with FEC

## Ordering Information



Part No.	Data Rate	Fiber	Distance*2	Interface	Temp.	DDMI
EOLQ-161HG-02-1	103Gbps	SMF	2km	LC	0~+70°C	Yes

\*1: For the latest certification information, please check with Eoptolink.

\*2: Over G.652 SMF.

\*The product image is only for reference purpose.

## Quality

Eoptolink Technology has passed many quality system verifications, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service. For latest certification/accreditation numbers, please, contact us.



## Notice

Eoptolink reserves the right to make changes or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## Eoptolink Technology Inc., Ltd.

Add: No.127 West Wulian Street, Shuangliu District, Chengdu City 610213, P.R.China.

Tel: +86-028-6708 7983 (HQ); +86-028-6708 7999

Fax: +86-028-6708 7979

Email:sales@eoptolink.com

<http://www.eoptolink.com/>