PRODUCT DETAILS

Eoptolink's 100G 500m SFP-DD Optical Transceiver



EOLSD-131HG-O-5H-36 Series

Single-Mode, 100G SFP-DD With LC interface



Product Description

Eoptolink's SFP-DD transceiver module is designed for use in 100 Gigabit Ethernet links over 500m single mode fiber. The module incorporates 1 channel optical signal, on 1311nm center wavelength, operating at 100Gbps data rate. This module has 2 independent electrical input/output channels which can convert 2 channels of 50Gbps (PAM4) electrical input data to 1 channel of 100Gbps (PAM4) optical signal, and also can convert 1 channel of 100Gbps (PAM4) optical signal to 2 channels of 50Gbps (PAM4) electrical output data. The electrical interface of the module is compliant with the 100GAUI-2 and SFP-DD MSA.

Features

- Supports 100Gbps
- IEEE802.3cd 100GBASE-DR Specification
 Compliant
- Single 3.3V Power Supply
- Power Dissipation < 3.5W</p>
- Up to 500m over SMF with FEC
- SFP-DD MSA Compliant
- 2x53.125Gbps(PAM4) electrical interface
- LC duplex connector

- Commercial Case Temperature Range
 Of 0°C to 70°C
- I²C Interface with Integrated Digital
 Diagnostic Monitoring
- Safety Certification: TUV/UL/FDA*1
- RoHS Compliant

Applications

- 100G Ethernet
- Data center



Ordering Information

Part No.	Data Rate	Fiber	Distance*2	Interface	Temp.
EOLSD-131HG-O-5H-36	100Gbps	SMF	500m	LC	0~+70℃

^{*1:} For the latest certification information, please check with Eoptolink.

^{*2:} Over SMF.

^{*}The product image is only for reference purpose.

Quality

Eoptolink Technology has passed many quality system verifications, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service. For latest certification/accreditation numbers, please, contact us.

















Notice

Eoptolink reserves the right to make changes or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. Eoptolink makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Eoptolink Technology Inc., Ltd.

Add: No.127 West Wulian Street, Shuangliu District, Chengdu City 610213, P.R.China.

Tel: +86-028-6708 7983 (HQ); +86-028-6708 7999

Fax: +86-028-6708 7979 Email: sales@eoptolink.com

http://www.eoptolink.com/