


Data sheet

Page 1 of 3

UV LED**EOLD-400-545 HP**

Rev. 02, 2014

Radiation	Type	Case
Ultraviolet	Resin mold packaged	5 mm plastic lens

Description:	
	Dimension in mm *High power *High-speed *High reliability

Maximum Ratings

 $T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Test Conditions	Symbol	Value	Unit
Forward current		I_F	25	mA
Peak forward current	$t < 0.1 \text{ ms}, t/T < 1/10$	I_{FM}	100	mA
Reverse current	$V_R = 5 \text{ V}$	I_R	85	mA
Power dissipation		P_D	100	mW
Operating temperature range		T_{amb}	-30 to +80	°C
Storage temperature range		T_{stg}	-30 to +85	°C
Lead soldering temperature	< 5 s, 3 mm from case	T_{slg}	260	°C

Optical and Electrical Characteristics

 $T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F = 20 \text{ mA}$	3	3.2	4	V
Radiant power	Φ_e	$I_F = 20 \text{ mA}$	21		29	mW
Peak wavelength	λ_p	$I_F = 20 \text{ mA}$	400		410	nm
Viewing angle	ϕ	$I_F = 20 \text{ mA}$		40		deg.
Spectral bandwidth at 50%	$\Delta\lambda_{0.5}$	$I_F = 20 \text{ mA}$	10		20	nm



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

Data sheet


Page 2 of 3

UV LED


EOLD-400-545 HP

Rev. 02, 2014


■ Forward voltage vs. Forward current




■ Forward current vs. Relative output power



■ Ambient temperature vs. Relative output power



■ Ambient temperature vs. Forward voltage





Data sheet**Page 3 of 3**

Rev. 02, 2014

UV LED**EOLD-400-545 HP**

- Ambient temperature vs.
Allowable forward current

- Spectrum



- Directivity

