



C Band UL DNC Switch Specifications



This document is the sole property of LP Technologies, Inc. The release of data contained in this document and the reproduction of this document in whole or in part, without the written permission of LP Technologies, Inc. is prohibited. The specs for this product are only tentative and are subject to change

Input Frequency	5925 – 6425 MHz
Output Frequency	1000 – 1500 MHz
Output Harmonics	<-30 dBc Typical, <-20 dBc Max
Output Spectrum	Non-Inverted, single conversion
LO Frequency	4925 MHz
LO Phase Noise	<-35 dBc/Hz @ 10 Hz <-70 dBc/Hz @ 100 Hz <-90 dBc/Hz @ 1 KHz <-92 dBc/Hz @ 10 KHz <-102 dBc/Hz @ 100 KHz <-122 dBc/Hz @ 1 MHz With External Reference Connected
Max Input	0 dBm, No Damage
Gain	15 dB +/- 2 dB
Gain Flatness	+/- 1.5 dB
Output Power P1dB	10 dBm
IMD3	-50 dBc, -10 dBm/tone 20 MHz apart
Group Delay	3 nSec, max peak to peak
Spurs	-50 dBc, output -10 dBm, signal related
Image Rejection	50 dB typical, 45 dB Max

Noise Figure	12 dB Typical, 15 dB Max
Impedance	50 Ohms
VSWR	2.5:1 Max, RF Port 1.7:1 Max, IF Port
Internal Reference	10 MHz
Internal Ref. Stability	+/- 3 ppm Over Temp, 0 to +50C
Internal Ref. Aging	+/- 1 ppm First Year max
Switch Network	4:1 Network, 4 RF inputs, 1 IF output
Switching Speed	100 μ s
Dimensions	19" Rack Mount 2RU
RF Connectors	SMA
LAN TCP/IP Interface	RJ-45 10Base-T, 100Base-TX
I/O Connector	RS-232C female connector
Temperature Range	0 to +50C