

SC5505A

6 GHz Dual Channel Signal Source for PXI Express

The SC5505A is a single slot, 3U, PXI Express 6 GHz dual channel CW signal source. The two channels provide independent frequency generation from 25 MHz to 6 GHz in frequency steps of 1 Hz. Both channels have a common internal 10 MHz TCXO reference, which can be phase locked to an external source for frequency synchronization.

The SC5505A has very low phase noise of better than -115 dBc/Hz at 10 kHz offset from a 1 GHz carrier. Using a unique multiple phase-locked loop architecture, phase spurs are kept below -70 dBc across the tuning range, even at 1 Hz step resolution. Harmonics are typically less than 30 dBc, and spurious signals are kept below -70 dBc. Channel-to-channel isolation is better than 70 dB.

The SC5505A is designed with the intent of being paired with SignalCore IQ modulators and demodulators such as the SC5412A and SC5312A respectively, to form RF transceivers. It also serves well as LO sources for multiple single stage downconverters or a dual stage downconverter. Due to its low spurious content and low phase noise, it is an ideal choice as a clock source for fast DAC and ADC applications, especially those that require variable sampling rates. Its compact size and instrument grade performance make the SC5505A an ideal RF source for many modern applications including wireless test, radar, digital clocking, instrumentation, academic research, and defense.



Product Features

- Low residual phase noise better than -115 dBc/Hz at 10 kHz offset, -140 dBc/Hz at 1 MHz offset, measured on 1 GHz carrier
- Low phase spurious content < -70 dBc
- 25 MHz to 6 GHz output range
- 1 Hz tuning resolution (exact frequency)
- < -50 dBm to +10 dBm leveled output
- Spurious signals < -70 dBc typical
- Channel isolation > 70 dB
- Automatic level control

SC5505A SPECIFICATIONS

TECHNICAL SPECIFICATIONS (AT 25°C AMBIENT, SINE WAVEFORM)

SPECTRAL SPECIFICATIONS

RF output frequency range ¹	25 MHz to 6 GHz
Internal reference	
Stability ²	±2.5 ppm
Aging	< 1 ppm after 1 year
Phase locking range	±5 ppm
Tuning	
Resolution	1 Hz
Speed (settled to .1 ppm) ³	< 500 us

Sideband phase noise (dBc/Hz)

Offset	RF Frequency			
	100 MHz	1 GHz	3 GHz	6 GHz
100 Hz	-107	-87	-85	-83
1 kHz	-119	-99	-98	-97
10 kHz	-135	-115	-110	-105
100 kHz	-136	-116	-111	-106
1 MHz	-150	-140	-130	-124
10 MHz	-150	-150	-149	-147

Sideband phase spurious signals

< 100 kHz	-65 dBc typical
> 100 kHz	-70 dBc typical

AMPLITUDE SPECIFICATIONS

Output RF range	-50 dBm to +10 dBm
Max output level	+16 dBm typical
Amplitude resolution	0.1 dB
2 nd order harmonics (0 dBm) ⁴	< -30 dBc
Output level accuracy	
> -30 dBm to +10 dBm	< ±0.5 dB
< -30 dBm	< ±0.75 dB

TERMINAL SPECIFICATIONS

LO output terminals	
Impedance	50 Ω
Connector type	SMA female
Coupling	AC
Reference input terminal	
Impedance (single ended)	50 Ω
Connector type	SMA female
Coupling	AC
Frequency	10 MHz
Amplitude range	-5 dBm to +10 dBm
Lock range	±5 ppm
Reference output terminal	
Impedance (single ended)	50 Ω
Connector type	SMA female
Coupling	AC
Frequency	10 MHz
Amplitude	+3 dBm
Communication interface	PXI Express
Power consumption	+12 V @ 1.5 A +3.3 V @ 0.2 A
Weight	1 lb
Dimensions (W x H x D, max envelope)	0.8" x 5.1" x 7.2"
Warranty	3 years parts and labor on defects in materials or workmanship

ENVIRONMENTAL

Operating temperature ⁵	-10 °C to +55 °C
Operating relative humidity	10% to 90%, non-condensing
Operating shock	30g, half-sine pulse, 11ms duration
Operating vibration	5 Hz to 500 Hz, 0.31 g _{rms}
Altitude	2000 m max (maintaining 25 °C ambient temperature)

ORDER INFORMATION

7100035-01	SC5505A, 6 GHz Dual Channel Signal Source for PXI Express
------------	---

Specifications are subject to change without notice. For the most recent product specifications, please visit www.signalcore.com.

- (1) Typically tunable from 23.5 MHz to 6150 MHz
- (2) Internal reference is a TCXO. For better accuracies and stability SignalCore recommends phase-locking to a precision external source
- (3) For step change of less than 100 MHz
- (4) Harmonic levels are specified for frequencies greater than 350 MHz. At lower RF frequencies the harmonic levels could be as high as -12 dBc.
- (5) The PXIe chassis must be capable of cooling 30W per module slot under these temperatures

Rev 2.0