

PM MPO Patchcord

PM Fiber MPO

Type: MPO-MPO, MT-FA, MPO Fanouts

Support up to 12F, 16F, customized products are available

Application:

Connect with trunk cable on one end, with equipment port on the other end

Connect with transfer module on one end, with equipment port on the other end

Tehchnical SpecificationJ

GRADE	STANDARD	HIGH
ALIGNMENT WAVELENGTH	1310 /1550nm	
FIBER TYPE	Conring PM13-U25D / PM15-U25D	
MAX INSERTION LOSS*1	0.7dB	12F:0.35dB, 16F:0.5dB
MIN EXTINCTION RATIO*1	18dB	20dB
TYPICAL OPTICAL RETURN LOSS	PC>20dB, APC≥60dB	
CONNECTOR TYPE	MPO/MTP/MT (12F、16F)	
KEY ALIGNMENT	Slow / Fast AXIS	
FAN-OUT END	FA/FC/LC/SC	
FAN-OUT MAX INSERTION LOSS	FC/LC/SC 0.3dB	
FAN-OUT END KEY ALIGNMENT	Slow / Fast Axis	
OPERATING TEMPERATURE	0 to 70℃	
STORAGE TEMPERATURE	-40 to 85℃	

*1,EACH CABLE INCLUDES INDIVIDUAL TEST DATA

Ordering Information

PMMPOPC-112-3456-788

11	Center Wamwlength	13=1310nm,15=1550nm
2	Grade	S=Standard, H=Hight
3	END 1 Type	1=12F MPO, 2=12F MPO, 3=16F MT, 4=16F MT
4	END 1 Key Alignment	1=Slow Aixs, 2= Fast Axis
5	END 2 Type	1=MPO, 2=MT, 3=FA, 4=FC/APC, 5=FC/UPC, 6=LC/APC 7=LC/UPC, 8=SC/APC, 9=SC/UPC
6	END 2 Key Alignment	1=Slow Aixs, 2= Fast Axis
7	Pigtail Type	0=bare fiber, 1=900μm loss tube, 2=3.0mm loss tube
88	Fiber Length	0.5=0.5m, 0.8=0.8m, 1=1m, 2=2m, 3=3m