

GD030**50V, DC – 6.0GHz, 30W GaN HEMT****FEATURES**

- Operating Frequency Range: DC to 6.0GHz
- Operating Drain Voltage: 28V & 50V
- Maximum Output Power (P_{SAT}): 50W
- Bare die shipped in Gel-Pak containers
- Suitable for CW, Pulsed, Linear applications
- 100% KGD DC Production Tested



1.63 x 0.75 mm Die

DESCRIPTION

The GD030 is a 50W (P3dB) unmatched discrete GaN-on-SiC HEMT which operates from DC to 6.0GHz on a 50V supply rail. The wide bandwidth of the GD030 makes it suitable for a variety of applications including cellular infrastructure, radar, communications, and test instrumentation, and can support CW, linear and pulse operations.

Bare die are shipped in Gel-Pak containers for safe transport and storage.

Typical Performances Measured Loadpull 1 Tone pulsed CW (10% duty cycle, 100 μ s width) in DFN 6x3 package, *2nd Harmonics NOT optimized*

- (1) Optimum Peak Power at 2.5dB in compression
- (2) Optimum Peak Efficiency at 2.5dB in compression

V_{ds}=50V, I_{dq}= 47 mA, T_A = 25°C

Frequency (MHz)	P _{out} ⁽¹⁾ (dBm)	Gain ⁽²⁾ (dB)	Eff ⁽²⁾ (%)
1000	46.2	23.7	65.2
1400	46.6	21.5	67.7
1800	46.7	20.8	64.7
2200	46.8	20.3	61.9
2600	46.9	18.9	66.1
3000	46.9	18.7	64.8
4000	46.9	17	64.5
5000	46.6	14.2	59.7
6000	46.8	13.5	60.8

V_{ds}=28V, I_{dq}= 47 mA, T_A = 25°C

Frequency (MHz)	P _{out} ⁽¹⁾ (dBm)	Gain ⁽²⁾ (dB)	Eff ⁽²⁾ (%)
1000	43.7	20.2	68.9
1400	44.2	19.9	68
1800	44.4	19.4	66.9
2200	44.2	18.7	64
2600	44.4	17.1	68
3000	44.4	16.9	66.7
4000	44.3	14.9	65.7
5000	44	12.8	61.3
6000	44.2	11.3	63.3

GD030

50V, DC – 6.0GHz, 30W GaN HEMT

ABSOLUTE MAXIMUM RATINGS^(1, 2)

Parameter	Rating	Symbols and Units
Drain Source Voltage	150	V_{DS} (V)
Gate Source Voltage	-8 to +2	V_{GS} (V)
Operating Voltage	55	V_{dsq} (V)
Junction Temperature	+225	T_{JUNC} (°C)
Storage Temperature	-65 to +150	$T_{STORAGE}$ (°C)


1. Exceeding any of these limits may cause permanent damage to this device or seriously limit the life time (MTTF)

2. GalliumSemi does not recommend sustained operation above maximum operating conditions.

ELECTRICAL SPECIFICATIONS: $T_A = 25^\circ\text{C}$

Parameter	Min.	Typ.	Max.	Symbols and Units	Test conditions
Frequency Range	DC		6000	MHz	
DC Characteristics					
Drain Source Breakdown Voltage	150			V_{BDSS} (V)	
Drain Source Leakage Current		1.93		I_{DLK} (mA)	$V_{gs} = -8V, V_{ds} = 50V$
Gate Threshold Voltage	-3.4		-1.5	V_{GS} (V)	$V_{ds} = 50V$
Operating Conditions					
Gate Bias Voltage		-2.5		V_{GSQ} (V)	
Drain Voltage		50		V_{DSQ} (V)	
Quiescent Drain Current		47		I_{DQ} (mA)	

BLOCK DIAGRAM



GD030


50V, DC – 6.0GHz, 30W GaN HEMT

THERMAL AND RELIABILITY INFORMATION -CW ^(1, 2): T_c = 85°C

Parameter	Test condition	Value	Units	Notes
Channel Temperature, T _{ch}	Pdiss 9 W	126.6	°C	
R _{th} die		2.63	°C/W	
MTTF		>1.0E+10	Hrs	
Channel Temperature, T _{ch}	Pdiss 18 W	173.4	°C	
R _{th} die		2.88	°C/W	
MTTF		1.0E+10	Hrs	
Channel Temperature, T _{ch}	Pdiss 28 W	232	°C	
R _{th} die		3.2	°C/W	
MTTF		1.0E+07	Hrs	

1.Assumes eutectic attach using 1mil low temp solder, mounted to a 8 mil DFN package.

2:Thermal Resistance using Finite Element Analysis (FEA) simulation, calibrated with Infrared measurement on surface temperature.



GD030

50V, DC – 6.0GHz, 30W GaN HEMT

LOADPULL MEASUREMENT, Vds= 50V Idq = 47 mA

Die packaged in DFN 6x3, Measured 1 Tone Pulse CW, pulse width 100us, duty cycle 10%

For Optimum Peak Power @ 2.5dB Compression

Freq-MHz	Zin_F0	ZI_F0	Gain-dB	Pout-dBm	Pout-W	Eff-%	AMPM-deg
1000	4.2 j -13.2	21.1 j 4.4	22.6	46.2	42.3	58.4	1
1200	3.0 j -11.0	17.4 j 7.7	22.3	46.5	45.4	60.4	1.8
1400	2.5 j -8.7	16.3 j 7.9	21.7	46.6	46.2	60.2	2
1600	2.5 j -7.3	12.8 j 4.8	19.5	47	50.2	54.5	3.2
1800	1.9 j -5.5	15.2 j 5.8	19.9	46.7	47.2	55.6	2.3
2000	2.3 j -4.6	14.0 j 4.1	18.9	46.6	45.6	50.8	2.2
2200	1.8 j -3.3	13.9 j 4.6	18.1	46.8	47.6	53.1	2.7
2400	1.6 j -2.1	12.5 j 7.1	18	46.7	46.4	56.6	3.1
2800	1.7 j -0.3	11.5 j 5.2	17.7	47	50.6	57	1.1
3000	1.7 j 0.6	11.6 j 3.0	16.8	46.9	49	53.1	0.8
3500	1.8 j 2.6	9.3 j 1.4	15.5	46.8	48.1	50.2	-0.2
4000	1.7 j 4.7	7.9 j 1.1	15.3	46.9	48.7	53.7	-1.3
4500	1.7 j 6.5	7.7 j -1.0	13.4	46.7	47.5	48.6	-1.9
5000	1.8 j 9.1	7.0 j -0.5	13.7	46.6	46.2	54.5	-1.9
5500	2.0 j 10.5	6.1 j -2.5	12.7	46.7	47	54.9	-1.8
6000	2.5 j 14.3	7.2 j -5.0	11.8	46.8	48.4	52.5	-1.1

For Optimum Peak Efficiency @ 2.5dB Compression

Freq-MHz	Zin_F0	ZI_F0	Gain-dB	Pout-dBm	Pout-W	Eff-%	AMPM-deg
1000	2.6 j -11.5	24.9 j 13.0	23.7	45.9	38.9	65.2	-0.9
1200	2.5 j -9.8	20.9 j 14.0	23.1	46.1	40.7	65.8	0.5
1400	2.2 j -7.4	22.8 j 18.4	21.5	45.7	37.7	67.7	3.4
1600	2.1 j -5.1	17.5 j 19.1	21.1	45.4	34.9	68.3	-0.6
1800	1.7 j -4.3	15.9 j 14.7	20.8	46.1	41.4	64.7	2.2
2000	2.1 j -3.5	18.0 j 16.4	19.4	45.9	38.7	61.9	4.2
2200	1.4 j -2.4	12.9 j 12.4	20.3	46.2	41.3	61.9	1.6
2400	1.2 j -1.1	10.6 j 14.0	19.7	45.6	36.2	61.2	1.6
2800	1.3 j 0.6	9.1 j 13.5	18.4	45.7	37.4	65.1	1.5
3000	1.1 j 1.8	8.9 j 12.4	18.7	45.5	35.6	64.8	0.2
3500	1.1 j 3.7	5.8 j 7.2	17.6	45.8	38.7	63.4	-1.2
4000	1.0 j 5.7	4.9 j 5.9	17	45.5	35.5	64.5	-2.1
4500	1.3 j 7.3	4.4 j 3.6	15.4	45.7	37.3	61.8	-1.9
5000	1.3 j 9.6	4.7 j 1.1	14.2	45.9	39.4	59.7	-2.7
5500	1.5 j 11.3	3.0 j -0.3	13.9	44.8	30.2	60.7	-2.7
6000	1.8 j 15.1	3.5 j -2.2	13.5	45.4	34.9	60.8	-0.9

GD030

50V, DC – 6.0GHz, 30W GaN HEMT

LOADPULL MEASUREMENT, $V_{ds}=28V$ $I_{dq}=47\text{ mA}$

Die packaged in DFN 6x3, Measured 1 Tone Pulse CW, pulse width 100us, duty cycle 10%

For Optimum Peak Power @ 2.5dB Compression

Freq-MHz	Zin_F0	ZI_F0	Gain-dB	Pout-dBm	Pout-W	Eff-%	AMPM-deg
1000	4.6 j -13.3	12.2 j -2.2	20.6	43.7	23.3	55.2	0.4
1200	3.7 j -11.0	12.3 j -1.0	19.7	43.9	24.8	57.1	1.4
1400	2.9 j -8.8	11.5 j 0.8	18.8	44.2	26.5	60.7	3.5
1600	2.9 j -7.1	10.4 j -0.8	18	44.4	27.4	56.1	0.6
1800	2.3 j -5.5	11.0 j 0.2	18.3	44.4	27.3	57.7	1.1
2000	2.1 j -4.3	11.5 j 0.7	17.8	44.1	25.8	56	1.6
2200	2.0 j -3.2	10.8 j -0.7	17	44.2	26.5	54.9	1.1
2400	1.8 j -2.1	10.7 j 0.3	16.8	44.2	26.1	56.1	0.7
2800	1.4 j 0.0	9.9 j 0.7	16.2	44.4	27.7	60.1	0.2
3000	1.5 j 0.9	9.4 j 0.3	16.4	44.4	27.5	60.4	-1.3
3500	1.6 j 2.9	7.9 j -1.0	15	44.4	27.2	58.1	-1.9
4000	1.4 j 5.1	7.1 j -1.3	14.5	44.3	26.8	60.9	-2.9
4500	1.9 j 6.7	8.2 j -3.9	12.4	44.2	26.1	53.6	-2.3
5000	1.4 j 9.5	5.9 j -4.7	12	44	25.4	57.2	-3.4
5500	1.8 j 10.9	6.6 j -6.1	10.9	44	25.9	57.3	-2.7
6000	2.2 j 14.8	7.9 j -7.1	10.6	44.2	26.5	58	-1.3

For Optimum Peak Efficiency @ 2.5dB Compression

Freq-MHz	Zin_F0	ZI_F0	Gain-dB	Pout-dBm	Pout-W	Eff-%	AMPM-deg
1000	3.5 j -11.7	20.0 j 1.7	20.2	43	20.4	68.9	0.1
1200	2.5 j -8.5	20.1 j 7.6	20.4	42.6	18.5	67.6	2.4
1400	2.3 j -7.5	19.3 j 8.4	19.9	42.8	19.2	68	3.1
1600	2.3 j -4.8	17.9 j 10.4	18.4	42.5	17.9	68.6	0
1800	1.5 j -3.9	13.7 j 8.0	19.4	43.2	21.1	66.9	0.7
2000	1.7 j -3.4	15.2 j 7.7	18	43.3	21.6	62.8	3
2200	1.1 j -1.8	10.6 j 7.6	18.7	43.2	20.7	64	0.1
2400	1.4 j -1.3	11.0 j 8.7	17.5	42.8	19	62.7	0.9
2800	1.1 j 1.2	9.3 j 8.1	16.8	42.9	19.6	67	-0.5
3000	1.0 j 2.1	8.7 j 7.1	16.9	42.7	18.8	66.7	-1.5
3500	1.1 j 3.5	6.6 j 2.5	15.3	43.7	23.9	66.2	-3
4000	1.1 j 5.8	6.1 j 1.9	14.9	43.2	21	65.7	-3.4
4500	1.3 j 7.7	4.6 j 0.5	13.6	42.8	19	64	-5
5000	1.3 j 9.8	5.1 j -1.8	12.8	43	19.9	61.3	-4.3
5500	1.4 j 11.5	3.7 j -4.1	11.6	42.8	19.5	63.1	-7.3
6000	1.7 j 15.4	4.2 j -6.0	11.3	43.2	21	63.3	-4.9

GD030

50V, DC – 6.0GHz, 30W GaN HEMT


LOADPULL MEASUREMENT NOTES

Source and Load impedance @ 2nd Harmonic are set to 10 Ohms

With proper 2nd Harmonic termination, expect +5% Efficiency for Source and similar with Drain 2nd Harmonic.

Z_{LOAD} : Measured Impedance presented to the output of the device in the reference plane

Z_{IN} : Measured input Impedance at the input of the device in the reference plane




Raw data and full Loadpull measurement report available at request: sales@galliumsemi.com


GD030 **50V, DC – 6.0GHz, 30W GaN HEMT**

BROADBAND S-PARAMETERS MEASUREMENT, $V_{ds}= 28 \text{ \& 50V}$ $I_{dq} = 47 \text{ mA}$
 Die packaged in DFN 6x3, Measured 1 Tone CW

S Parameters (Mag-dB)




S11 & S22 0.4-6 GHz




GD030 **50V, DC – 6.0GHz, 30W GaN HEMT**

BROADBAND S-PARAMETERS MEASUREMENT, $V_{ds} = 28$ & $50V$ $I_{dq} = 47$ mA
 Die packaged in DFN 6x3, Measured 1 Tone CW

Maximum Available Gain



K Factor



GD030**50V, DC – 6.0GHz, 30W GaN HEMT****GaN HEMT BIASING SEQUENCE**

To turn the transistor ON


1. Set V_{GS} to -5V
2. Turn on V_{DS} to normal operation voltage (50V)
3. Slowly increase V_{GS} to set I_{DQ} current (47mA)
4. Apply RF power

To turn the transistor OFF

1. Turn the RF power off
2. Decrease V_{GS} to -1.5V
3. Turn off V_D . Wait a few seconds for drain capacitor to discharge
4. Turn off V_{GS}

GD030 **50V, DC – 6.0GHz, 30W GaN HEMT**

DIE DIMENSIONS



Bond Pads

Pad nb.	Description	Dimensions
1, 5, 6, 7	Not connected	
2, 3, 4	RF Input / Gate Voltage	0.110 x 0.305
8	RF Output / Drain Voltage	0.110 x 1.459
Backside	Source/ Ground	0.755 x 1.630

Notes:

1. All dimensions are in millimeter
2. Die thickness is 75 um
3. Bond pad metallization: gold
4. Backside metallization: gold

GD030**50V, DC – 6.0GHz, 30W GaN HEMT****HANDLING PRECAUTIONS**

Parameter	Symbol	Class	Test Methodology
ESD* – Human Body Model	HBM	Class 1A (250 V)	ANSI/ESDA/JEDEC Standard JS-001
ESD* – Charged Device Model	CDM	Class C3 (1500 V)	ANSI/ESDA/JEDEC Standard JS-002

* Tested in DFN 3x6 package



GD030**50V, DC – 6.0GHz, 30W GaN HEMT**

CONTACT INFORMATION

To request latest information and samples, please contact us at:

Web: <https://www.galliumsemi.com/>

Email: sales@galliumsemi.com

IMPORTANT NOTICE

Even though Gallium Semiconductor believes the material in this document to be reliable, it makes no guarantees as to its accuracy and disclaims all responsibility for any damages that may arise from using its contents. Contents in this document are subject to change at any time without prior notice. Customers should obtain and validate the most recent essential information prior to making orders for Gallium Semiconductor products. The information provided here or any use of such material, whether about the information itself or anything it describes, does not grant any party any patent rights, licenses, or other intellectual property rights. Without limiting the generality of the aforementioned, Gallium Semiconductor products are neither warranted nor approved for use as crucial parts in medical, lifesaving, or life-sustaining applications, or in any other applications where a failure would likely result in serious personal injury or death.

GALLIUM SEMICONDUCTOR DISCLAIMS ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO SUCH PRODUCTS, WHETHER BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE.