

S6700-32CQ 32-Port 400G Data Center Managed Ethernet Switch



- 32 * 40G/100G/400G Q SFP2 8 optical interfaces
- 2 * 10 G SFP+ optical interfaces
- Hardware level multiple protection ensures continuous operation of equipment and stable network without disconnection
- Multiple network management methods for simple and easy network maintenance
- High end chips with more stable and powerful performance
- Supports one-stop management on the Apollo cloud platform



Description

Overview

Adopts advanced hardware architecture with 32* 400GE ports



Switch backplane bandwidth

12.8Tbps

Working Humidity

10% ~ 90% RH non-condensing

Packet forwarding

5600Mpps

Dimensions (W × D × H)

440mm×450mm×44mm

switch port

32 * 40G/100G/400G Q SFP2 8 optical interfaces

2 * 10 G SFP+ optical interfaces

S6700-32CQ

32-Port 400G Data Center Managed Ethernet Switch

S6700-32CQ is a new generation Full 400G Ethernet switch designed for enterprise Data center and campus LAN networks, providing high-throughput, high-density 400GE interfaces, larger buffer and lower latency.



APPLICABLE SCENARIOS

S6700-32QF is a new generation Full 100G Ethernet switch designed for enterprise data center and campus LAN networks.



High-End Cyber Cafes



Campuses



High-Speed Enterprise Network

HIGHLIGHT FEATURES

32 * 40G/100G/400G Q SFP2 8 optical interfaces;
2 * 10 G SFP+ optical interfaces;




HIGH END CHIPS

- High end chips with more stable and powerful performance
- High end chips that can significantly improve network data processing speed

Fore-edge

APOLLO CLOUD SYSTEM MANAGEMENT PLATFORM

Supports one-stop management on the Apollo cloud platform.





Specifications

Hardware Specification:	
Network Interface	32 * 40G/100G/400G Q SFP28 optical interfaces 2 * 10 G SFP+ optical interfaces 1 * Console port 1 * Management port 1 * USB port
Redundant Design	Support 2 pluggable power, 1 + 1 backup mode Support 6 pluggable fans
Switching Capacity	12.8Tbps
Packets Forwarding	5600Mpps
RAM	8GB
FLASH	128MB
SSD	128GB
Port Buffer	48MB
Power Supplier	AC: 90V~264V, rated voltage 100V~127V or 200~240V

	High voltage DC: 180-300V, rated voltage 240V
Dimension	WxDxH : 440×450×44mm
Environment	Operating temperature : 0 °C~ 40 °C Storage temperature : -40°C~ 70°C Operating humidity : 10% ~ 90% RH non condensing Storage humidity : 10% ~ 90% RH non condensing
Safety Regulations	CE/ ROHS/ FCC
Software Specifications:	
VLAN	Support 4K VLAN Support 1:1 and N:1 802.1p based VLAN Mapping Support VLANs based on MAC, protocol, and IP Support Guest VLAN, Voice VLAN Support QinQ, selective QinQ
IP	Support 256K IPv4/64K IPv6 Support IPv4/IPv6 static routing Support GRE tunnel Support ECMP Support policy routing Support OSPF, IS-IS, BGP and other IPv4 Dynamic routing protocols Support OSPFv3, IS-ISv6, BGP4+ and other IPv6 Dynamic routing protocols Support IGMP , IGMP Snooping , MLD Snooping
VXLAN	Supports VXLAN Layer 2 switching, routing switching, and Layer 3 gateway Support EVPN VXLAN Support IPv6 VXLAN over IPv4
EVPN	Support EVPN Support MP-BGP, EVPN's RR function Support symmetric IRB
Reliable Features	Support STP/RSTP/MSTP Support BPDU protection, Root protection, and Loop protection; Support for BPDU Tunnel Support BPDU tunnel Support RIP BFD session binding Static routing, VRRP, OSPF, IS-IS, BGP,
Stacking	Supports horizontal virtualization technology and unified management of multiple devices
IPv6	Support ND(Neighbour Discovery) , support PMTU Support time period based ACLs Support IPv6 Ping , Traceroute

	Support dual stacks of IPv4 and IPv6; Support multiple tunnel technologies Supports ACLs based on source IPv6 address, destination IPv6 address, layer 4 port, protocol type, etc
Software Specifications:	
QoS	Support L2-L4 packet filtering function, providing filtering based on MAC, IP, port, protocol, IP ToS, 802.IP priority, VLAN ID, SVLAN ID, VLAN range, etc. Support time period based ACLs Support Bandwidth throttling based on stream/VLAN (single speed and dual color) Support streaming of single speed tricolor and dual speed tricolor Support flow based priority scheduling and priority mapping Support scheduling algorithms such as SP/PQ, DRR, SP/PQ+DRR, etc Supports 8 QoS hardware priority queues per port Support 802.1p , DSCP/ToS priority Support queue cache management strategies such as end of queue discarding and WRED
Security Features	Support hierarchical management of user permissions and hierarchical protection of command lines Support 802.1x,RADIUS,TACACS+ Support user level quantity limit Support user binding (port, source MAC, source IP address access control) Support SNMP login terminal restrictions Support SSH2.0 Support IP source guard Support black hole MAC Supports MAC address limit Support anti ARP and DDoS attacks
Maintenance	Support Console,Telnet,SSH protocols Support SNMP V1/V2/V3,support standard MIB Support Netconf management protocol,support REST API Support for the gNMI protocol,support Telemetry protocol Support FTP/TFTP Support unified management of logs, alarms, and debugging information Support user action logs Support RMON Supports port mirroring and stream mirroring Supports BootROM upgrade and remote online upgrade, supports hot patches

Additional information

Models	S6700-32QF
Series	Data Center Series

Related products



S6700-64CQ 64-Port 400G Data Center Managed Ethernet Switch



S6700-32QF 32-Port 100G Data Center Managed Ethernet Switch



S6700-48YF-8QF-H 100G uplink 48-Port 25G Data Center Managed...



S6700-48TF-8QF-H 100G uplink 48 port 25G Data center switches